



26 Additional removable chairs may be added to the stage floor in front of the first rows of permanent seating.

Floor to ceiling clearance: 13'4" (not including lighting trusses)

Lighting Pipes hang 1'6" from ceiling

**KEY**

PAR 56 WFL 500W	PAR 56 WFL 300W
PAR 64 WFL 500W	S4 JR-50 575W
COLORSOURCE LED	ALT 3.5X6 500W
GORO COLOR	ALTMAN 6X9 575W
SIMMER CHANNEL	6" FRESNEL 500W
HOUSE LT 40W	iPAR 64 LED

THIS DRAWING REPRESENTS THE INTELLECTUAL PROPERTY OF FORRST TRIMBLE AND IS INTENDED TO COMMUNICATE INSTRUMENT PLACEMENT. IT IS NOT THE DESIGNER'S DUTY TO DETERMINE THE STRUCTURAL OR ELECTRICAL APPROPRIATENESS OF THIS VENUE AND HE SHALL NOT ASSUME ANY RESPONSIBILITY FOR IMPROPER ENGINEERING, CONSTRUCTION, RIGGING, HANDLING OR USE.

ALL MATERIALS AND CONSTRUCTION TECHNIQUES MUST COMPLY WITH THE MOST STRINGENT APPLICABLE FEDERAL, AND LOCAL CODES INCLUDING: FIRE, SAFETY, STRUCTURAL, AND ELECTRICAL. THE CONCEPTS, DESIGN, AND DOCUMENTS SHOWN OR REFERRED TO HEREIN, ARE THE SOLE AND EXCLUSIVE PROPERTY OF BOB STEINECK AND ASSOCIATES AND MAY ONLY BE USED FOR THE PROJECT AND CLIENT FOR WHICH THEY HAVE BEEN PREPARED. THIS DRAWING WAS PREPARED FOR VENUE PRODUCTION PERSONNEL AND ELECTRICIANS TO UNDERSTAND THE PLACEMENT OF LIGHTING INSTRUMENTS ONLY.

Production Title	
Carnegie Stage Rep Plot	
Designer	Director
Drawn By	Scale 1/4"=1'0"
Venue Carnegie Stage	Drawing No. 1 of 1
Date	
CAD File Name carnegie stage rep plot	